

LEFOO

浮球开关 FLOAT SWITCH



HT-M15-18 FLOAT SWITCH




技术参数/TECHNICAL DATA

1. 额定电压: AC 110/220V
 2. 最大电流: AC 5A
 3. 频率: 50/60Hz
 4. 最高使用温度: 120℃
 5. 保护等级: IP68
1. Rated voltage: AC 110/220V
 2. Max. Current: AC 5A
 3. Frequency: 50/60Hz
 4. Max. Using Temperature: 120℃
 5. Protection Degree: IP68

描述/DESCRIPTIONS

1. 自动补水模式 Auto-fill-water modes.




将控制器的蓝色线与水泵相连,黑色线与零线相连,棕色线不接并绝缘。

Connect the control's blue line to electric pump, black line is connected to zero-line, brown line can not be connected and should be insulated.



2. 自动排水模式
Auto-drainage and lack-water protection modes



将控制器的棕色线与水泵相连,黑色线与零线相连,蓝色线不接并绝缘。

Connect the control's brown line to electric pump, black line is connected to zero-line, blue line can not be connected and should be insulated.

LEFOO

浮球液位控制器 WATER LEVEL CONTROLLER



HT-70AB FLOAT SWITCH



技术参数/TECHNICAL DATA

1. 额定电压: AC 110/220V
 2. 最大电流: AC 15(3)A
 3. 频率: 50/60Hz
 4. 最高使用温度: 60℃
 5. 蓄水使用A1和A2触点
 6. 排水使用B1和B2出点
1. Rated voltage: AC 110/220V
 2. Max. Current: AC 15(3)A
 3. Frequency: 50/60Hz
 4. Max. Using Temperature: 60℃
 5. illing use A1 and A2 Point
 6. Draining use B1 and B2 Point

外形与尺寸 Outline dimension

